INSTRUCTIONS



Extra Wide Tall-Ette[®] Toilet Seat

with **Lok-in-El[®]** Bracket and Armrest Bars

Catalog Number 72589-1000

The 72589-1000 Tall-Ette[®] Elevated Toilet Seat comes completely assembled with the **Lok-In-El**[®] bracket and armrest bars permanently attached.

To Install on Toilet:

- 1. Loosen nuts on the screws that hold the toilet seat and lid to the toilet.
- 2. Lift the toilet seat to a raised position and pull up.
- Slide the Lok-In-El[®] bracket tongue under the seat bracket so that the side section fits between the toilet seat screws and the two narrow sections fit outside of the screws.
- 4. Tighten the nuts on the screws to secure the seat and bracket. The Tall-Ette® Elevated Toilet Seat should be in contact with the bowl. The bottom flange fits inside the rim of the toilet bowl.

Screw Cap Screw Lok-In-El® Toilet Bowl Tank Removed for Illustration Purpose Only

Caution:

Do not use this model without the Lok-In-El® Bracket.

Do not remove the Lok-In-El® Bracket.

Do not use the Tall-Ette® Elevated Toilet Seat if it does not fit into the toilet bowl rim.



6 INDUSTRIAL ROAD • PEQUANNOCK, NJ 07440-1993 USA

973-628-7600 • fax 973-305-0841 • email custservice@maddak.com • www.maddak.com